



HOUSE-POOL PROTECTION DEVICE INSTALLATION
Residential Pool/Spa Permit Requirements
City of Carrollton Building Inspection Department

The attached **Certification of House-Pool Protection Device Installation** form is utilized to assist homeowners and contractors in complying with the requirements of residential pool and/or spa permits.

By utilizing this form, the Building Inspection Department will require the code requirements for swimming pool/spa door protection. The homeowner accepts the responsibility of complying with the current Carrollton Construction Code regulations by his/her written documentation implemented by this form.

The following steps must be completed in order for the form to be accepted:

1. One of the two options must be initialed. If both devices are used on different doors, both options should be initialed.
2. The homeowner's name must be printed legibly on the appropriate line.
3. The site address must be printed legibly on the appropriate line.
4. A Notary must NOTARIZE the homeowner's signature.
5. The Notary must complete the final section of the document.
6. The form must be returned to Building Inspection Department at 1945 E. Jackson Road, Carrollton, TX 75006.



**BUILDING INSPECTION
DEVELOPMENT SERVICES**



Certification of House-Pool Protection Device Installation

I certify that I am the homeowner at _____ and that one of the following swimming pool protection devices will be installed between all doors leading from the house and garage into the swimming pool area at or before the pool final inspection (initial one or both if provided).

- 1. All doors leading into the pool area are equipped with an alarm that sounds continuously for at least thirty (30) seconds within seven (7) seconds after the door and its screen, if present, are opened. It must be capable of providing a sound pressure level capable of being heard throughout the house during normal household activities. The alarm shall automatically reset under all conditions and be equipped with a manual means, such as a touch pad or switch, to temporarily deactivate the alarm for a single opening. Such deactivation shall last not longer than 15 seconds. The deactivation device shall be located at least 54 inches above the threshold of the door.
- 2. All doors leading into the pool area are equipped with self-closing and self-latching devices installed within the release mechanism located a minimum of 54 inches above the floor.

Print name of homeowner: _____

Signature of homeowner: _____ Date: _____

THE STATE OF TEXAS §

COUNTY OF _____ §

BEFORE ME, the undersigned authority, a Notary Public in and for the State of Texas, on this day personally appeared _____, known to me to be the person whose name is subscribed to the foregoing instrument and acknowledged to me that he executed same for the purposes and consideration therein expressed.

GIVEN UNDER MY HAND AND SEAL OF OFFICE this the _____ day of _____, 20__.

Notary Seal:

Notary Public in and for the State of Texas

Texas Penal Code Section 37.10 states that a person commits a Class A misdemeanor if they knowingly make false entries in, or false alteration of, a governmental record or makes, present or uses any record, document, or thing with knowledge of its falsity and with intent that it be taken as a genuine governmental record.



**BUILDING INSPECTION
DEVELOPMENT SERVICES**